

## NORGREN ISO Roundline cylinder double acting series RM/8000/N2



- Magnetic piston as standard
- Conforms to ISO 6432
- High strength, double crimped end cap design
- Corrosion resistant
- Buffer or adjustable cushioning
- Nose mounting nut and piston rod locknut as standard

### Characteristics

**Series:** RM/8000/M

**Function:** Double acting

**Magnetic:** Yes

**Barrel material:** Stainless steel

**Operating temperature:** -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
RM/8016/N2/100	Mechanical	16	100	M 5		1 / 10	11578990
RM/8020/N2/25	Mechanical	20	25		G1/8	1 / 10	11579051
RM/8025/N2/50	Mechanical	25	50		G1/8	1 / 10	11579129
RM/8025/N2/100	Mechanical	25	100		G1/8	1 / 10	11579128

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.