



NORGREN Repairable roundline cylinder double acting series M/6000/J

Characteristics

Series: Martonair

Type: M/6000

Function: Double acting

Magnetic: No

Barrel material: Aluminium

Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	in	bar	
M/6020/J/12	Mechanical	20	12	G1/8	2 / 10	11576648
M/6020/J/20	Mechanical	20	20	G1/8	2 / 10	11577245
M/6020/J/25	Mechanical	20	25	G1/8	2 / 10	11577246
M/6020/J/50	Mechanical	20	50	G1/8	2 / 10	11577247
M/6020/J/100	Mechanical	20	100	G1/8	2 / 10	11577244
M/6025/J/20	Mechanical	25	20	G1/8	2 / 10	11577260
M/6025/J/25	Mechanical	25	25	G1/8	2 / 10	11577261
M/6025/J/50	Mechanical	25	50	G1/8	2 / 10	11577262

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.