

NORGREN Universal air bellow single acting series M/31000



- Frictionless operation
- No maintenance or lubrication
- Ideal for short stroke, high-force applications
- High vibration isolation level
- Easy, compact installation

Characteristics

Series: M/31000

Function: Single acting

Operating temperature: -40 / 70 °C

Manufacturer ID	Stroke length	Port Size	Operating pressure		Article
	mm		in	bar	
M/31061	55	G1/2	0 / 8		11575545
M/31062	115	G1/2	0 / 8		23209169
M/31081	75	G1/2	0 / 8		23209354
M/31082	175	G1/2	0 / 8		23209513
M/31101	100	G1/2	0 / 8		11575549
M/31102	225	G1/2	0 / 8		11575550
M/31103	330	G1/2	0 / 8		11575551
M/31121	100	G1/2	0 / 8		11575552
M/31122	225	G1/2	0 / 8		23209128
M/31123	330	G1/2	0 / 8		23214017
M/31162	315	G1/2	0 / 8		11575558
M/31141	100	G1/2	0 / 8		11575555
M/31142	265	G1/2	0 / 8		11575556
M/31143	380	G1/2	0 / 8		11575557

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.