



SUGIYAMA Lock switch for HP hollow pin chain ANSI Simplex

Characteristics

Type: ANSI 80-1

Pitch in	Pitch mm	Norm	Model	ISO reference	ANSI	Material	Article
1/2	12.7	ANSI B29.1 - ISO 606 - DIN 8188	Simplex	08A-1	40-1	Steel	23545207
5/8	15.875	ANSI B29.1 - ISO 606 - DIN 8188	Simplex	10A-1	50-1	Steel	23545228
3/4	19.05	ANSI B29.1 - ISO 606 - DIN 8188	Simplex	12A-1	60-1	Steel	23545251
1	25.4	ANSI B29.1 - ISO 606 - DIN 8188	Simplex	16A-1	80-1	Steel	23545272
1	25.4	ANSI B29.1 - ISO 606 - DIN 8188	Simplex	16A-1	80-1	Steel	23545271
1 1/4	31.75	ANSI B29.1 - ISO 606 - DIN 8188	Simplex	20A-1	100-1	Steel	23545149

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.