

## PFERD Grinding stone, cylindrical ZY hardness L

Mounted points in hardness L are manufactured from a grain mix of white and dark red aluminium oxide and a high-quality resinoid bond.

This relatively soft bond contains grinding additives and, in combination with the grain mix, leads to exceptionally high stock removal rates and a long tool life.

The hardness L is particularly suited for surface work on stainless steel (INOX) and for general use on non-ferrous metals and bronze.

- The maximum permitted rotational speed refers to the unsupported shank length of 10 mm



Lining material	Granulation	Diameter mm	Hardness	Length mm	Pin connection mm	Article
Aluminium oxide	24	32	L	16	6	12742615
Aluminium oxide	24	32	L	40	6	12742617
Aluminium oxide	24	32	L	40	8	12742619
Aluminium oxide	24	40	L	20	6	12742623
Aluminium oxide	24	50	L	25	6	12742628
Aluminium oxide	24	50	L	40	8	23872113
Aluminium oxide	30	16	L	32	6	12742608
Aluminium oxide	30	20	L	25	6	12742610
Aluminium oxide	30	20	L	40	6	12742612
Aluminium oxide	30	25	L	25	6	23871943
Aluminium oxide	30	25	L	32	6	23871950
Aluminium oxide	30	40	L	10	6	12742622
Aluminium oxide	30	50	L	13	6	12742625
Aluminium oxide	46	10	L	20	6	12742604
Aluminium oxide	46	10	L	32	6	12742606
Aluminium oxide	60	20	L	25	6	23871922

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.