

PFERD Grinding stone, cylindrical ZY hardness N



Mounted points in hardness N are manufactured from regular aluminium oxide and a high-quality resinoid bond.

This relatively hard bond contains grinding additives, which in combination with tough regular aluminium oxide and the hard bond allow high stock removal rates and excellent tool life.

The hardness N is particularly suited for edge grinding on stainless steel (INOX). It is characterized by cool grinding and high dimensional stability.

- The maximum permitted rotational speed refers to the unsupported shank length of 10 mm

Lining material	Granulation	Diameter mm	Hardness	Length mm	Pin connection mm	Article
						14591698
						14591697
						23429155
						23149182
						23429156
						23429153
						23429152
Aluminium oxide	24	32	N	16	6	12742598
Aluminium oxide	24	32	N	40	6	12742600
Aluminium oxide	24	50	N	25	6	23429157
Aluminium oxide	30	20	N	40	6	12742596
Aluminium oxide	30	40	N	10	6	12742602
Aluminium oxide	30	50	N	8	6	23872109
Aluminium oxide	46	10	N	20	6	12742593
Aluminium oxide	46	10	N	32	6	23429151
Aluminium oxide	60	16	N	32	6	23871895

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.