

## PFERD Grinding stone, conical, KE hardness O

Mounted points in hardness O consist of pink aluminium oxide in a vitrified bond. These tools are characterized by a very long tool life and good stock removal rate due to the combination of wear resistant grain and a hard bond.



The hardness O is particularly suited for use on edges and for deburring work on steel components.  
 - The maximum permitted rotational speed refers to the unsupported shank length of 10 mm

Lining material	Granulation	Diameter mm	Hardness	Length mm	Pin connection mm	Article
						14591699
Aluminium oxide	30	20	O	32	6	23429148
Aluminium oxide	30	25	O	25	6	23872224
Aluminium oxide	30	25	O	45	6	23872257
Aluminium oxide	30	25	O	70	6	23872269
Aluminium oxide	46	10	O	25	6	23429146
Aluminium oxide	46	13	O	13	6	23872217
Aluminium oxide	60	16	O	16	6	23872219
Aluminium oxide	60	20	O	32	6	23872235
Aluminium oxide	60	25	O	25	6	23872225
Aluminium oxide	60	25	O	45	6	23872258
Aluminium oxide	80	10	O	25	6	23872243

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.