

PFERD Grinding stone, spherical, KU hardness O



Mounted points in hardness O consist of pink aluminium oxide in a vitrified bond.

These tools are characterized by a very long tool life and good stock removal rate due to the combination of wear resistant grain and a hard bond.

The hardness O is particularly suited for use on edges and for deburring work on steel components.

- The maximum permitted rotational speed refers to the unsupported shank length of 10 mm

| Lining material | Granulation | Diameter mm | Hardness | Pin connection mm | Article |
|-----------------|-------------|----------------|----------|----------------------|----------|
| Aluminium oxide | 30 | 20 | O | 6 | 23872151 |
| Aluminium oxide | 46 | 8 | O | 3 | 23872168 |
| Aluminium oxide | 46 | 10 | O | 3 | 23872165 |
| Aluminium oxide | 46 | 13 | O | 3 | 23872170 |
| Aluminium oxide | 46 | 32 | O | 6 | 23872162 |
| Aluminium oxide | 60 | 5 | O | 3 | 23872137 |
| Aluminium oxide | 60 | 16 | O | 6 | 23872147 |
| Aluminium oxide | 60 | 25 | O | 6 | 23872157 |
| Aluminium oxide | 80 | 8 | O | 6 | 23872139 |
| Aluminium oxide | 80 | 10 | O | 6 | 23872164 |
| Aluminium oxide | 100 | 3 | O | 3 | 23872133 |
| Aluminium oxide | 100 | 5 | O | 3 | 23872136 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.