

## GUHRING NR HSS-E Fire roughing end mill type 2218




Design: DIN 844-K, 30°, up to dia. 28 mm with centre cut.

HSS-E PM has outstanding durability [greater edge stability, more wear-resistant] and a longer tool life.

Cutting speed approx. 50% higher than for non-coated tools. Dry machining possible.

Application: Particularly suitable for roughing steels up to 1000 N/mm<sup>2</sup>.



Description	Article
Milling cutter sh. DIN844HSSE-PM FIRE type NRf 6mm	W90A-22180060
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 10mm	W90A-22180100
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 12mm	W90A-22180120
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 14mm	W90A-22180140
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 16mm	W90A-22180160
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 18mm	W90A-22180180
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 20mm	W90A-22180200
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 25mm	W90A-22180250
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 32mm	W90A-22180320
Rough.end mill sh. DIN844HSSE-PM FIRE type NRf 8mm	W90A-22180080

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.