



Milling cutter insert SDMT .. Type 2999



ISO milling insert 15° positive with radius 0.8 mm

delta Can only be supplied as a whole packaging unit.

Cutting values for P Steel:

Cutting speed VC: 165?225 m/min.

Feed fz: 0.1?0.25 mm/tooth

Cutting depth: 1?10 ap/mm

Cutting values for M Stainless:

Cutting speed VC: 95?135 m/min.

Feed fz: 0.1?0.19 mm/tooth

Cutting depth: 1.0?7.5 ap/mm

Cutting values for K Cast iron:

Cutting speed VC: 155?210 m/min.

Feed fz: 0.1?0.25 mm/tooth

Cutting depth: 1?10 ap/mm

Cutting values for S super-alloy:

Cutting speed VC: 30?65 m/min.

Feed fz: 0.1?0.15 mm/tooth

Cutting depth: 1?6 ap/mm

Description	Article
Milling ind. insert 15degpositive SDMT 120508SR F PMK 9130	12594970
Milling ind. insert 15degpositive SDMT 120508SR F U 9145	12594971

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.