

GUHRING Slot drills (3-fluted) type 3651

Design: Type N, 30°, from dia. 3.0 mm with central cut.



Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9 as well as for peripheral milling.

Cutting speed approx. 50% higher than with non-coated tools. Dry machining possible.

Characteristics

Type: Keyway cutter

Holding system: Weldon

DIN standard: 327

Tolerance: e8/h10

Type	Diameter		Maximum working length	Shaft diameter	Total length	Holding system	Material	DIN standard	Tolerance	Article
	mm	mm								
Keyway cutter	4	7	6	51	Weldon	m42	327	e8/h10	W90A-21560400	
Keyway cutter	5	8	6	52	Weldon	m42	327	e8/h10	W90A-21560500	
Keyway cutter	8	11	10	61	Weldon	m42	327	e8/h10	W90A-21560800	
Keyway cutter	10	13	10	63	Weldon	m42	327	e8/h10	W90A-21561000	
Keyway cutter	14	16	12	73	Weldon	m42	327	e8/h10	W90A-21561400	
Keyway cutter	16	19	16	79	Weldon	m42	327	e8/h10	W90A-21561600	
Keyway cutter	20	22	20	88	Weldon	m42	327	e8/h10	W90A-21562000	

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.