

GUHRING Slot drills (3-fluted) type 3664

Characteristics



Type: Milling cutter with shank

Holding system: Weldon

DIN standard: 844K

Tolerance: e8/h10

Type	Diameter	Maximum working length	Shaft diameter	Total length	Holding system	Material	DIN standard	Tolerance	Article
	mm	mm	mm	mm					
Keyway cutter	3	8	6	52	Weldon	m42	844K	e8/h10	11983494
Keyway cutter	5	13	6	57	Weldon	m42	844K	e8/h10	11983498
Keyway cutter	6	13	6	57	Weldon	m42	844K	e8/h10	11983500
Keyway cutter	7	16	10	66	Weldon	m42	844K	e8/h10	11983502
Keyway cutter	8	19	10	69	Weldon	m42	844K	e8/h10	11983504
Keyway cutter	9	19	10	69	Weldon	m42	844K	e8/h10	11983505
Keyway cutter	10	22	10	72	Weldon	m42	844K	e8/h10	11983507
Keyway cutter	11	22	12	79	Weldon	m42	844K	e8/h10	11983508
Keyway cutter	12	26	12	83	Weldon	m42	844K	e8/h10	11983510
Keyway cutter	14	26	12	83	Weldon	m42	844K	e8/h10	11983512
Keyway cutter	15	26	12	83	Weldon	m42	844K	e8/h10	11983513
Keyway cutter	16	32	16	92	Weldon	m42	844K	e8/h10	11983515
Keyway cutter	18	32	16	92	Weldon	m42	844K	e8/h10	11983516
Milling cutter with shank							844K		11983496
Milling cutter with shank							844K		11983517

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.