

FORMAT Milling cutter with shank, N HSSco TiAIN type 2179




Design: Type N, DIN 844-L, 30°, up to dia. 28 mm with centre cut.

Application: Can be used for peripheral and end milling.

Cutting speed approx. 50% higher than with non-coated tools. Dry machining possible.

HSS-E-PM has outstanding durability [greater edge stability, more wear-resistant] and a longer tool life.



Characteristics

Type: Milling cutter with shank

DIN standard: 844L

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Milling cutter with shank	24	6	68	844K	W90A-21790500
Milling cutter with shank	24	6	68	844L	W90A-21790600
Milling cutter with shank	30	10	80	844K	W90A-21790700
Milling cutter with shank	38	10	88	844K	W90A-21790900
Milling cutter with shank	45	10	95	844L	W90A-21791000
Milling cutter with shank	38	10	88	844L	W90A-21790800
Milling cutter with shank	53	12	110	844L	W90A-21791200
Milling cutter with shank	53	12	110	844L	W90A-21791400
Milling cutter with shank	63	16	123	844L	W90A-21791800
Milling cutter with shank	63	16	123	844L	W90A-21791600
Milling cutter with shank	75	20	141	844L	W90A-21792000
Milling cutter with shank	90	25	166	844L	W90A-21792500

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.