

## FORMAT Milling cutter with shank, N HSS-E TiAlN type 2176




Design: HSS-E PM, type N, DIN 844-K, 30°, TiAlN-coated, with centre cut.

HSS-E PM has outstanding durability [greater edge stability, more wear-resistant] and a longer tool life.

Cutting speed approx. 50% higher than for non-coated tools. Dry machining possible.

Application: Can be used for peripheral and end milling.



### Characteristics

**Type:** Milling cutter with shank

**DIN standard:** 844K

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Milling cutter with shank	7	6	51	844K	12049385
Milling cutter with shank	3	6	49	844K	12049384
Milling cutter with shank	11	6	55	844K	23110244
Milling cutter with shank	13	6	57	844K	23110245
Milling cutter with shank	13	6	57	844K	23110246
Milling cutter with shank	8	6	52	844K	23110243
Milling cutter with shank	22	10	72	844K	23110248
Milling cutter with shank	19	10	69	844K	23110247
Milling cutter with shank	26	12	83	844K	23110249
Milling cutter with shank	26	12	83	844K	23110250
Milling cutter with shank	32	16	92	844K	23110251
Milling cutter with shank	32	16	92	844K	23110252
Milling cutter with shank	38	20	104	844K	23110253
Milling cutter with shank	45	25	121	844K	23110254

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.