

## FORMAT Key way mill N HSSCo TiAlN type 2155




Design: HSS-E PM, type N, DIN 844-K, 30°, TiAlN-coated, with centre cut.

HSS-E PM has outstanding durability [greater edge stability, more wear-resistant] and a longer tool life.

Cutting speed approx. 50% higher than for non-coated tools. Dry machining possible.

Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9 as well as for peripheral milling.



### Characteristics

**Type:** Keyway cutter

**DIN standard:** 844K

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Keyway cutter	8	6	52	844K	W90A-21550300
Keyway cutter	13	6	57	844K	W90A-21550600
Keyway cutter	11	6	55	844K	W90A-21550450
Keyway cutter	10	6	54	844K	W90A-21550350
Keyway cutter	13	6	57	844K	W90A-21550500
Keyway cutter	13	6	57	844K	W90A-21550550
Keyway cutter	11	6	55	844K	W90A-21550400
Keyway cutter	16	10	66	844K	W90A-21550700
Keyway cutter	16	10	66	844K	W90A-21550650
Keyway cutter	19	10	69	844K	W90A-21550850
Keyway cutter	22	10	72	844K	W90A-21551000
Keyway cutter	19	10	69	844K	W90A-21550800
Keyway cutter	19	10	69	844K	W90A-21550900
Keyway cutter	26	12	83	844K	W90A-21551200
Keyway cutter	26	12	83	844K	W90A-21551500
Keyway cutter	26	12	83	844K	W90A-21551300
Keyway cutter	26	12	83	844K	W90A-21551400
Keyway cutter	22	12	79	844K	W90A-21551100
Keyway cutter	32	16	92	844K	W90A-21551800
Keyway cutter	32	16	92	844K	W90A-21551600
Keyway cutter	38	20	104	844K	W90A-21552000
Keyway cutter	45	25	121	844K	W90A-21552500

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.