


FORMAT Key way mill N HSSCo type 2145



Design: Type N, 30°, from dia. 3.0 mm with central cut.

Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9 as well as for peripheral milling.

< Ø 3,0 mm



Characteristics

Type: Keyway cutter

DIN standard: 327

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Keyway cutter	8	6	52	327	23108688
Keyway cutter	7	6	51	327	23108687
Keyway cutter	8	6	52	327	23109362
Keyway cutter	5	6	49	327	23108686
Keyway cutter	8	6	52	327	23108689
Keyway cutter	4	6	48	327	23108685
Keyway cutter	11	10	61	327	23108692
Keyway cutter	13	10	63	327	23108693
Keyway cutter	11	10	61	327	23109365
Keyway cutter	10	10	60	327	23108690
Keyway cutter	10	10	60	327	23109363
Keyway cutter	11	10	61	327	23108691
Keyway cutter	16	12	73	327	23108697
Keyway cutter	16	12	73	327	23108695
Keyway cutter	19	16	79	327	23108699
Keyway cutter	22	20	88	327	23108701
Keyway cutter	26	25	102	327	23108704
Keyway cutter	26	25	102	327	23108706
Keyway cutter	26	25	102	327	23108707
Keyway cutter	32	32	112	327	23108708

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.