

FORMAT Key way mill N HSS-E TiAlN type 2113



Design: Type N, DIN 327-D, 30°, with central cut.


Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9.

HSS-E PM has outstanding durability (greater edge stability, more wear-resistant) and a longer tool life. Cutting speed approx. 50% higher than for non-coated tools. Dry machining possible.

Characteristics

Type: Keyway cutter

DIN standard: 327



Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Keyway cutter	8	6	52	327	W90A-21130500
Keyway cutter	5	6	49	327	W90A-21130250
Keyway cutter	7	6	51	327	W90A-21130400
Keyway cutter	8	6	52	327	W90A-21130550
Keyway cutter	8	6	52	327	W90A-21130600
Keyway cutter	7	6	51	327	W90A-21130450
Keyway cutter	5	6	49	327	W90A-21130300
Keyway cutter	6	6	50	327	W90A-21130350
Keyway cutter	4	6	48	327	W90A-21130200
Keyway cutter	13	10	63	327	W90A-21131000
Keyway cutter	11	10	61	327	W90A-21130800
Keyway cutter	16	12	73	327	W90A-21131400
Keyway cutter	16	12	73	327	W90A-21131200
Keyway cutter	19	16	79	327	W90A-21131800
Keyway cutter	19	16	79	327	W90A-21131600
Keyway cutter	22	20	88	327	W90A-21132000

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.