

FORMAT Key way mill N HSS-E TiAlN type 2149




Design: Type N, 30°, from dia. 3.0 mm with central cut.

Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9 as well as for peripheral milling.

HSS-E PM has outstanding durability (greater edge stability, more wear-resistant) and a longer tool life.

Cutting speed approx. 50% higher than for non-coated tools. Dry machining possible.

< Ø 3,0 mm



Characteristics

Type: Keyway cutter

DIN standard: 327

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Keyway cutter	8	6	52	327	W90A-21490500
Keyway cutter	8	6	52	327	W90A-21490600
Keyway cutter	7	6	51	327	W90A-21490400
Keyway cutter	8	6	52	327	W90A-21490550
Keyway cutter	7	6	51	327	W90A-21490450
Keyway cutter	5	6	49	327	W90A-21490300
Keyway cutter	6	6	50	327	W90A-21490350
Keyway cutter	4	6	48	327	W90A-21490200
Keyway cutter	5	6	49	327	W90A-21490250
Keyway cutter	11	10	61	327	W90A-21490800
Keyway cutter	10	10	60	327	W90A-21490650
Keyway cutter	11	10	61	327	W90A-21490850
Keyway cutter	10	10	60	327	W90A-21490700
Keyway cutter	13	10	63	327	W90A-21491000
Keyway cutter	11	10	61	327	W90A-21490900
Keyway cutter	16	12	73	327	W90A-21491200
Keyway cutter	16	12	73	327	W90A-21491500
Keyway cutter	16	12	73	327	W90A-21491300
Keyway cutter	13	12	70	327	W90A-21491100
Keyway cutter	16	12	73	327	W90A-21491400
Keyway cutter	19	16	79	327	W90A-21491800
Keyway cutter	19	16	79	327	W90A-21491600
Keyway cutter	22	20	88	327	W90A-21492000

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.