

## FORMAT Key way mill N HSS-E TiAlN type 2149




Design: Type N, 30°, from dia. 3.0 mm with central cut.

Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9 as well as for peripheral milling.

HSS-E PM has outstanding durability (greater edge stability, more wear-resistant) and a longer tool life.

Cutting speed approx. 50% higher than for non-coated tools. Dry machining possible.

< Ø 3,0 mm



### Characteristics

**Type:** Keyway cutter

**DIN standard:** 327

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Keyway cutter	8	6	52	327	12049325
Keyway cutter	8	6	52	327	12049327
Keyway cutter	7	6	51	327	12049323
Keyway cutter	8	6	52	327	12049326
Keyway cutter	7	6	51	327	12049324
Keyway cutter	5	6	49	327	12049321
Keyway cutter	6	6	50	327	12049322
Keyway cutter	4	6	48	327	12049319
Keyway cutter	5	6	49	327	12049320
Keyway cutter	11	10	61	327	12049330
Keyway cutter	10	10	60	327	12049328
Keyway cutter	11	10	61	327	12049331
Keyway cutter	10	10	60	327	12049329
Keyway cutter	13	10	63	327	12049333
Keyway cutter	11	10	61	327	12049332
Keyway cutter	16	12	73	327	12049335
Keyway cutter	16	12	73	327	12049338
Keyway cutter	16	12	73	327	12049336
Keyway cutter	13	12	70	327	12049334
Keyway cutter	16	12	73	327	12049337
Keyway cutter	19	16	79	327	12049340
Keyway cutter	19	16	79	327	12049339
Keyway cutter	22	20	88	327	12049341

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.