

## GUHRING Key way mill N HSSco Fire type 2156




Design: Type N, 30°, from dia. 3.0 mm with central cut.

Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9 as well as for peripheral milling.

Cutting speed approx. 50% higher than with non-coated tools. Dry machining possible.

< Ø 3,0 mm



### Characteristics

**Type:** Keyway cutter

**DIN standard:** 327

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Keyway cutter	5	6	49	327	12049344
Keyway cutter	7	6	51	327	12049345
Keyway cutter	8	6	52	327	12049347
Keyway cutter	11	10	61	327	12049348
Keyway cutter	13	10	63	327	12049349
Keyway cutter	16	12	73	327	12049351
Keyway cutter	16	12	73	327	12049350
Keyway cutter	19	16	79	327	12049353
Keyway cutter	22	20	88	327	12049354

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.