



Plastic floor element

•

#### Secure storage according to regulations

Suitable for water polluting liquids in all hazard classes.

Not approved for storing flammable liquids.

General building approval of DIBt Berlin.

•

#### High resistance

Resistant to acids, lye, oils and other corrosive hazardous materials.

Load-bearing capacity: 800 kg/m<sup>2</sup> (when load is distributed evenly).

•

#### Individual adjustment to space requirements

The combination of multiple base elements enables optimal, comprehensive soil protection.

Height 150 mm, directly accessible with barrel truck.

Combination options: PE floor element, order no. 3010.8263 and 3010.8265, with ramp made of polyethylene [accessories].

| Capacity<br>l | Length<br>mm | Width<br>mm | Height<br>mm | Article  |
|---------------|--------------|-------------|--------------|----------|
| 220           | 1500         | 1500        | 150          | 11823478 |
| 400           | 3000         | 1500        | 150          | 11823480 |
| 400           | 3000         | 1500        | 150          | 11823481 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.