



CEMO MULTI-tank, double-walled

MULTI-Tank double walled

- **High stability**
Low centre of gravity also increases the stability and improves handling/transport.
- **High portability**
Hard affiliated sheet steel pallet for accessing with forklift trucks or pallet trucks from four sides.
- **Solid construction**
Made of HDPE with integral galvanised sheet steel drip pan.
- **Storage without drip pan**
Suitable for fresh and waste oil with flash point > 55 °C.
Also approved in water protection areas without drip pan and for installation in buildings.
- **Easy filling**
Low height [up to 1000 litres], thus no foot stool is necessary for filling waste oil.
- **Accessories (standard)**
Level indicator, visual leak indicator, integrated handles.

Approved for transport according to ADR. Recurrent test after 2-1/2 years (see ADR 6.5.6.4.b). Transport approval for all IBC plastic is limited to 5 years.

Capacity l	Length mm	Width mm	Height mm	Weight kg	Article
400	730	700	1170	55	23862580
750	980	770	1460	82	23862551
1000	1280	800	1470	110	23862552
1500	1630	770	1870	165	23862581

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.