



## SKF Rod end Maintenance-free Steel/PTFE sintered bronze Internal thread right hand Series: SI..C


### Design:

Maintenance-free rod end with a threaded shank. With an open bearing (without seals), internal (female) right-hand thread.

### Sliding contact surface combination: Steel/PTFE sintered bronze

Suitable for heavy, constant direction loads, where low coefficient of friction is required; limited suitability for alternating loads, shock loads.

Rod end with steel/PTFE sintered bronze sliding contact surface combination contain a bearing from the standard assortment. The outer ring is staked in place in the housing.



### Characteristics

**Series:** SI..C

**Thread type:** Internal thread right hand

**Maintenance:** Maintenance-free

**Sliding contact surface:** Steel/PTFE sintered bronze

Manufacturer ID	Inner diameter mm	Thread size	Article
SI 6 C	6	M 6	23769684
SI 8 C	8	M 8	23769689
SI 10 C	10	M 10	23769661
SI 12 C	12	M 12	23769663
SI 15 C	15	M 14	23769665
SI 17 C	17	M 16	23769667
SI 20 C	20	M 20x1.5	23769669
SI 25 C	25	M 24x2	23769672
SI 30 C	30	M 30x2	23769674

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.