



## SKF Bearing washer Series: LS

### LS series universal washers

- Raceway surface is ground, while all other surfaces are turned are used for applications where accurate centring of the washers is not necessary or where low speeds are involved
- washer face opposite the side with the chamfers is the raceway surface and should face the rollers. are made of hardened carbon chromium bearing steel
- can be used as shaft or housing washers for needle roller thrust bearings in the AXK series
- can be used as shaft washers for bearings in the AXW series
- are available for  $6 \leq d \leq 160$  mm

### Characteristics

Series: LS

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
LS 0821	8	21	2.75	23766749
LS 1024	10	24	2.75	23766751
LS 1226	12	26	2.75	23766752
LS 1528	15	28	2.75	23766753
LS 1730	17	30	2.75	24003787
LS 2035	20	35	2.75	23766754
LS 2542	25	42	3	23766755
LS 3047	30	47	3	23766756
LS 3552	35	52	3.5	23766757
LS 4060	40	60	3.5	23766758
LS 4565	45	65	4	23766759
LS 5070	50	70	4	23766760
LS 5578	55	78	5	23766761
LS 7095	70	95	5.25	24003789
LS 85110	85	110	5.75	23766763
LS 90120	90	120	6.5	23766764

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.