PRESSOL Grease filling device

Grease filler valve

Design:

Due to the high sliding cover, the amount of grease which is still in the bucket can always be checked. The filling nozzle is placed obliquely, so that grease guns with obliquely inserted filler nipple can be filled easily. The large handle allows for easy removal of the grease sequence piston. Supplied with intake pipe, filler nipple M10 x 1 and dust cap on the filling nozzle secured with a chain for converting to grease guns of other makes.

Application:

For filling grease guns and pneumatic presses.

Characteristics

Type: 17 815

| Description | Article |
|---|----------|
| Grease fil. pump f. buck.180-210mm 5kg | 23429789 |
| Grease fil. pump f. buck.210-240mm 10kg | 23429790 |
| Grease fil. pump f. buck.240-270mm 15kg | 23429791 |
| Grease fil. pump f. buck.310-335mm 25kg | 23429792 |
| Grease fil. pump f. buck.365-385mm 50kg | 23429793 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: tools@eriks.be

Page 1/1

RC0221_0078_MVB_EN_02.06.2024