

PRESSOL PREMAXX pump 24V max. litres/min

PREMAxx barrel and container pump 230 V - max. 52 I/min

• Suitable for heating oil and diesel

For the filling of agricultural machines, construction machines, trucks, motor boats and utility vehicles Note: Not suitable for biodiesel!

Extraction height 7 to 15 m

For 200 I containers / max. 1000 I tanks, suction up to 2 m by way of integrated lever-operated cylinder pump Barrel adapter 50.80 mm [G 2"] and M64x4a.

Safe handling

Suction unit with integrated, constantly effective lifting protection (leak-proof) according to WHG Motor with thermo protection switch (against overload, self resetting) Illuminated power switch

Extensive extraction set

Complete with 4 m extraction hose with kink protection spring and dispenser valve 1.6 m suction hose with foot filter

Characteristics

Type: 23 734

Description	Article
PREMAxx 52I/min 230V-1AC-50Hz-EUS-ZVAB	11598487
PREMAxx-52I/min 230V-1AC-50Hz-EUS-ZVPP	11598486

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

Page 1/1

RC0221_0087_MVB_EN_26.06.2024