

E-COLL Multi-purpose grease

Multi-purpose grease

Product description

- with colloidal graphite -

Universal grease for lubricating rolling and friction bearings, even in mixed friction area, especially for all sliding speeds permissible for grease lubrication.

Reduces friction/wear even with high loads, protects lubricated parts from sea water.

Application areas

Ideal for agricultural machinery, construction equipment, excavators, trucks, tractors, stone crushers, semitrailers, etc.

Lifts, battery chargers, conveyor belts and water pumps.

Technical characteristics

With long-life workpiece combinations, emergency operating features, lithium-emulsified. Temperature resistance -30°C to +130°C.

Drop point: +190 °C, resin-free. Consistency index according to DIN 51818: NLGI grade 2. Possible designation according to DIN 51502: KPK2K-30.

Content	Article
kg	
0.4	23429937
1	12326727
	14572920

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: tools@eriks.be

Page 1/1

PR_RC0243_0041_MVB_EN_02.07.2024