



## MOLYKOTE G-Rapid Plus Assembly paste Kanrapid

- Solid lubricating paste with particularly low friction coefficient for assembly and running-in of metal components.
  - Low friction coefficient
- High load-carrying capacity
- Prevents seizure and scoring
- Suppresses stick-slip
- Reduces formation of fretting corrosion
- Provides emergency running performance.

### Characteristics

**Temperature range:** -35 / 450 °C

**Colour:** Black

### Application

- Suitable for the press-fit production of all types of machine elements, as a running-in lubricant for new machines and gears, as permanent lubrication of machine elements which are submitted to slight or intermittent movement only, as well as for drilling, sawing and thread-cutting; Used to lubricate threaded spindles, splined shafts, tooth gearing, worm gearing, moving screws, fittings, pumps, guides on machine tools, as well as for fitting of ball and roller bearings, pulleys, wheel flanges and bolts.

### Technical Information

**Temperature Range:**

- From -35 to +450°C

Volume	Content	Packaging	Article
l	kg		
0.4			23164853
	0.05	Pipe	23164854
	0.25		23360995
	0.25		23164305

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.