



FILTRATION GROUP Medium-pressure filter type Pi 340

Characteristics

Series: Pi 340

Temperature range [°C]: -10 / 120 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	50		Flange connection DN15	Bypass 7 bar	No		13522225
Pi 3405-010	50	350	Flange connection DN15		No		13522224
Pi 3405-014	50	350	Flange connection DN15		Optical 5 bar		13522228
Pi 3405-015	50	350	Flange connection DN15		Optical/Electrical 5 bar	250VAC/200VDC	13522229
Pi 3405-012	50	350	Flange connection DN15	Bypass 7 bar	Optical 5 bar		13522226
Pi 3405-013	50	350	Flange connection DN15	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522227
	80		Flange connection DN15	Bypass 7 bar	No		13522231
	80		Flange connection DN15	Bypass 7 bar	Optic		13522232
	80		Flange connection DN15	No bypass	No		13522230
	80		Flange connection DN15	No bypass	Optical/Electrical 5 bar	250VAC/200VDC	13522235
Pi 3408-014	80	350	Flange connection DN15		Optical 5 bar		13522234
Pi 3408-013	80	350	Flange connection DN15	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522233
	110		Flange connection DN15	No bypass	Optical 5 bar		13522239
Pi 3411-010	110	350	Flange connection DN15		No		13522236
Pi 3411-015	110	350	Flange connection DN15		Optical/Electrical 5 bar	250VAC/200VDC	13522240
Pi 3411-012	110	350	Flange connection DN15	Bypass 7 bar	Optical 5 bar		13522237
Pi 3411-013	110	350	Flange connection DN15	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522238
	150		Flange connection DN38	Bypass 7 bar	No		13522242
	150		Flange connection DN38	Bypass 7 bar	Optic		13522243
	150		Flange connection DN38	Bypass 7 bar	Optical/Electrical	250VAC/200VDC	13522244
	150		Flange connection DN38	No bypass	No		13522241
	150		Flange connection DN38	No bypass	Optical 5 bar		13522245
	150		Flange connection DN38	No bypass	Optical/Electrical 5 bar	250VAC/200VDC	13522246
	300		Flange connection DN38	Bypass 7 bar	No		13522247
Pi 3430-012	300	250	Flange connection DN38	Bypass 7 bar	Optical 5 bar		13522248
Pi 3430-013	300	250	Flange connection DN38	Bypass 7 bar	Optical/Electrical 5 bar	250VAC/200VDC	13522249
Pi 3430-014	300	315	Flange connection DN38		Optical 5 bar		13522250
Pi 3430-015	300	315	Flange connection DN38		Optical/Electrical 5 bar	250VAC/200VDC	13522251

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	450		Flange connection DN38	Bypass 7 bar	No		13522252
	450		Flange connection DN38	Bypass 7 bar	Optical/Electrical	250VAC/200VDC	13522254
	450		Flange connection DN38	No bypass	Optical/Electrical 5 bar	250VAC/200VDC	13522256
Pi 3445-012	450	250	Flange connection DN38	Bypass 7 bar	Optical 5 bar		13522253
Pi 3445-014	450	315	Flange connection DN38		Optical 5 bar		13522255

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.