

DANFOSS Orbitmotor 4K [4000] Series



Characteristics

Series: 4K [4000]

Direction of rotation: Clockwise and counterclockwise

Mounting flange	Drive shaft	Displacement cm ³ /r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
ISO 125-4	Cylindrical 40 mm	110	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1249	979120
ISO 125-4	Cylindrical 40 mm	130	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1248	979139
ISO 125-4	Cylindrical 40 mm	160	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1247	1011165
ISO 125-4	Cylindrical 40 mm	205	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1231	979155
ISO 125-4	Cylindrical 40 mm	245	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1245	980358
ISO 125-4	Cylindrical 40 mm	310	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1246	980366
ISO 125-4	Cylindrical 40 mm	395	190	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1236	980374
ISO 125-4	Cylindrical 40 mm	495	140	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1234	980382
ISO 125-4	Cylindrical 40 mm	625	115	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1235	980420
SAE-C 4 bolts	Cylindrical 40 mm	110	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1184	761516
SAE-C 4 bolts	Cylindrical 40 mm	130	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1185	761567
SAE-C 4 bolts	Cylindrical 40 mm	160	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1227	761656
SAE-C 4 bolts	Cylindrical 40 mm	205	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1224	974730
SAE-C 4 bolts	Cylindrical 40 mm	245	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1225	932302
SAE-C 4 bolts	Cylindrical 40 mm	310	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1189	838918
SAE-C 4 bolts	Cylindrical 40 mm	395	190	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1190	761869
SAE-C 4 bolts	Cylindrical 40 mm	495	140	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1267	1009908
SAE-C 4 bolts	Cylindrical 40 mm	625	115	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	109-1233	765023
Wheel flange	Tapered 1.5/8" [41,28 mm]	245	205	BSP female 3/4" BSP	BSP female 3/4" BSP	Side	110-1136	966630

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.