




GRUNDFOS CRN series vertical multistage centrifugal pump flange

Characteristics

Series: CRN

Material pump casing: Stainless steel



Nominal volume flow rate m³/h	Material quality	Nominal inner diameter	Medium temperature °C	Article
1.8	1.4408	DN25 - DN32	-20 / 120	23501944
1.8	1.4408	DN25 - DN32	-20 / 120	23501947
1.8	1.4408	DN25 - DN32	-20 / 120	23501930
1.8	1.4408	DN25 - DN32	-20 / 120	23501933
1.8	1.4408	DN25 - DN32	-20 / 120	23501945
1.8	1.4408	DN25 - DN32	-20 / 120	23501937
1.8	1.4408	DN25 - DN32	-20 / 120	23501948
1.8	1.4408	DN25 - DN32	-20 / 120	23501928
1.8	1.4408	DN25 - DN32	-20 / 120	23501934
1.8	1.4408	DN25 - DN32	-20 / 120	23501946
1.8	1.4408	DN25 - DN32	-20 / 120	23501929
1.8	1.4408	DN25 - DN32	-20 / 120	23501940
1.8	1.4408	DN25 - DN32	-20 / 120	23501943
1.8	1.4408	DN25 - DN32	-20 / 120	23501938
1.8	1.4408	DN25 - DN32	-20 / 120	23501941
1.8	1.4408	DN25 - DN32	-20 / 120	23501942
1.8	1.4408	DN25 - DN32	-20 / 120	23501931
1.8	1.4408	DN25 - DN32	-20 / 120	23501949
3	1.4408	DN25 - DN32	-20 / 120	23502018
3	1.4408	DN25 - DN32	-20 / 120	23501871
3	1.4408	DN25 - DN32	-20 / 120	23502016
3	1.4408	DN25 - DN32	-20 / 120	23501885
3	1.4408	DN25 - DN32	-20 / 120	23502019
3	1.4408	DN25 - DN32	-20 / 120	23502027
3	1.4408	DN25 - DN32	-20 / 120	23501873
3	1.4408	DN25 - DN32	-20 / 120	23502013
3	1.4408	DN25 - DN32	-20 / 120	23502024
3	1.4408	DN25 - DN32	-20 / 120	23502021
3	1.4408	DN25 - DN32	-20 / 120	23502012
3	1.4408	DN25 - DN32	-20 / 120	23502015
3	1.4408	DN25 - DN32	-20 / 120	23502026
3	1.4408	DN25 - DN32	-20 / 120	23502023
3	1.4408	DN25 - DN32	-20 / 120	23502020

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal volume flow rate m³/h	Material quality	Nominal inner diameter	Medium temperature °C	Article
3	1.4408	DN25 - DN32	-20 / 120	23501872
3	1.4408	DN25 - DN32	-20 / 120	23502014
3	1.4408	DN25 - DN32	-20 / 120	23502017
3	1.4408	DN25 - DN32	-20 / 120	23502011
3	1.4408	DN25 - DN32	-20 / 120	23501259
3	1.4408	DN25 - DN32	-20 / 120	23501121
3	1.4408	DN25 - DN32	-20 / 120	23502022
3	1.4408	DN25 - DN32	-20 / 120	23502025
5.8	1.4408	DN25 - DN32	-20 / 120	23501877
5.8	1.4408	DN25 - DN32	-20 / 120	23502074
5.8	1.4408	DN25 - DN32	-20 / 120	23502082
5.8	1.4408	DN25 - DN32	-20 / 120	23501098
5.8	1.4408	DN25 - DN32	-20 / 120	23501878
5.8	1.4408	DN25 - DN32	-20 / 120	23502085
5.8	1.4408	DN25 - DN32	-20 / 120	23501881
5.8	1.4408	DN25 - DN32	-20 / 120	23501875
5.8	1.4408	DN25 - DN32	-20 / 120	23502080
5.8	1.4408	DN25 - DN32	-20 / 120	23502086
5.8	1.4408	DN25 - DN32	-20 / 120	23502084
5.8	1.4408	DN25 - DN32	-20 / 120	23502083
10	1.4408	DN40	-20 / 120	23501392
10	1.4408	DN40	-20 / 120	23501354
10	1.4408	DN40	-20 / 120	23501393
10	1.4408	DN40	-20 / 120	23501356
10	1.4408	DN40	-20 / 120	23501359
10	1.4408	DN40	-20 / 120	23501387
10	1.4408	DN40	-20 / 120	23501357
10	1.4408	DN40	-20 / 120	23501390
10	1.4408	DN40	-20 / 120	23501395
10	1.4408	DN40	-20 / 120	23501358
10	1.4408	DN40	-20 / 120	23501355
10	1.4408	DN40	-20 / 120	23501389
10	1.4408	DN40	-20 / 120	23501391
10	1.4408	DN40	-20 / 120	23501394
10	1.4408	DN40	-20 / 120	23501388
10	1.4408	DN40	-20 / 120	23501396
17	1.4408	DN50	-20 / 120	23501411
17	1.4408	DN50	-20 / 120	23501446
17	1.4408	DN50	-20 / 120	23501443
17	1.4408	DN50	-20 / 120	23501449
17	1.4408	DN50	-20 / 120	23501440
17	1.4408	DN50	-20 / 120	23501450
17	1.4408	DN50	-20 / 120	23501412
17	1.4408	DN50	-20 / 120	23501445
17	1.4408	DN50	-20 / 120	23501442
17	1.4408	DN50	-20 / 120	23501444
17	1.4408	DN50	-20 / 120	23501448
17	1.4408	DN50	-20 / 120	23501441
17	1.4408	DN50	-20 / 120	23501447
21	1.4408	DN50	-20 / 120	23501309
21	1.4408	DN50	-20 / 120	23501302
21	1.4408	DN50	-20 / 120	23501305
21	1.4408	DN50	-20 / 120	23501275

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal volume flow rate m³/h	Material quality	Nominal inner diameter	Medium temperature °C	Article
21	1.4408	DN50	-20 / 120	23501310
21	1.4408	DN50	-20 / 120	23501308
21	1.4408	DN50	-20 / 120	23501274
21	1.4408	DN50	-20 / 120	23501304
21	1.4408	DN50	-20 / 120	23501301
21	1.4408	DN50	-20 / 120	23501307
21	1.4408	DN50	-20 / 120	23501306
30	1.4408	DN65	-40 / 120	23499203
30	1.4408	DN65	-40 / 120	23499208
30	1.4408	DN65	-40 / 120	23499209
30	1.4408	DN65	-40 / 120	23499206
30	1.4408	DN65	-40 / 120	23499204
30	1.4408	DN65	-40 / 120	23499207
30	1.4408	DN65	-40 / 120	23499210
30	1.4408	DN65	-40 / 120	23499205
45	1.4408	DN80	-40 / 120	23499257
45	1.4408	DN80	-40 / 120	23499256
45	1.4408	DN80	-40 / 120	23499255
45	1.4408	DN80	-40 / 120	23499258
64	1.4408	DN100	-40 / 120	23499295
64	1.4408	DN100	-40 / 120	23499296
64	1.4408	DN100	-40 / 120	23499297
				23502079
				23501880
				23501324
				23501879
				23501874
				23501856
				23502078
				23501876
				23502075
				23502076
				23502081
				23502073

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.