



NORGREN R07 series Pressure reduction valve in-line

- Ported regulators for general purpose pneumatic applications
- Relieving operation as standard
- Non-rising adjusting knob with snap-action lock

Characteristics

Series: R07

Flow rate: max. 7.5 l/s [G ¼", 10 bar]

Membrane material: PU

Material seal: NBR

Material housing: Zinc

Temperature range [°C]: -34 / 65 °C

Pressure range bar	Max. inlet pressure bar	Weight g	Article
0.3 / 7	20		11584667
0.3 / 10	20		11584674
0.1 / 0.7	20		11584668
0.3 / 10	20		11584673
0.1 / 0.7	20		13275314
0.3 / 3.5	20	130	11584670
0.3 / 7	20	130	11516907
0.1 / 0.7			11584663
0.3 / 7			11584666
0.3 / 3.5			11584669
0.3 / 3.5			11584664
0.3 / 3.5			12259436
0.3 / 3.5			11584665
0.3 / 7			11584671
0.1 / 0.7			11584675
0.1 / 0.7	20		11584682
0.3 / 10	20		11584688
0.3 / 7	20		11584680
0.3 / 7	20		11612104
0.3 / 10	20		11584689
0.3 / 3.5	20	130	11584684
0.3 / 7	20	130	11584686
0.3 / 3.5			11584679
0.1 / 0.7			11584681
0.3 / 7			11584690
0.1 / 0.7			11584677
0.3 / 3.5			11584683
0.3 / 7			11584685

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.