



LOWARA Submersible pump Series: DOMO roestvaststaal monofase

Characteristics

Series: DOMO

Frequency: 50Hz

Connection: Internal thread (BSPP)

Material pump casing: Stainless steel

Material quality: 1.4301

Pump casing material: Stainless steel SS 304 [1.4301]

Level of protection (IP value): IPX8

Insulation class acc. to IEC: F

Maximum flow rate l/min	Nominal volume flow rate m³/h	Max. immersion depth m	With float	Type of switch	Supply voltage	Length connecting cord m	Rotational speed rpm	Connection size	Article
15500	15.5	5	Yes	Model magnetic	1 x 230V AC	10	2850	1.1/2" [40]	13548903
15500	15.5	5	Yes	Float switch	1 x 230V AC	10	2850	1.1/2" [40]	13548875
19000	19	5	No		1 x 230V AC	10	2850	1.1/2" [40]	13548874
19000	19	5	Yes	Float switch	1 x 230V AC	10	2850	1.1/2" [40]	13548873
19000	19	5	Yes	Model magnetic	1 x 230V AC	10	2850	1.1/2" [40]	13548890
24000	24	5	No		1 x 230V AC	10	2850	2" [50]	13548879
24000	24	5	Yes	Model magnetic	1 x 230V AC	10	2850	2" [50]	13548904
24000	24	5	Yes	Float switch	1 x 230V AC	10	2850	2" [50]	13548878
27000	27	5	No		1 x 230V AC	10	2850	2" [50]	13548882
27000	27	5	Yes	Model magnetic	1 x 230V AC	10	2850	2" [50]	13548905
30000	30	5	No		1 x 230V AC	10	2850	2" [50]	13548877
30000	30	5	Yes	Float switch	1 x 230V AC	10	2850	2" [50]	13548876
30000	30	5	Yes	Model magnetic	1 x 230V AC	10	2850	2" [50]	13548891
36000	36	5	No		1 x 230V AC	10	2850	2" [50]	13548881
36000	36	5	Yes	Model magnetic	1 x 230V AC	10	2850	2" [50]	13548892

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.