



SKF Miniature ball bearing closure on one side

Miniature ball bearings are single-row deep groove ball bearings with a bore diameter of up to 10 mm. Single-row deep groove ball bearings are extremely versatile. They are simple in design, suitable for high to very high speeds, very robust and thus low-maintenance. Thanks to the deep grooves and the close contact between the grooves and the balls, deep groove ball bearings are extremely well suited to tolerate both radial loads and axial loads in both directions, even at high speeds. Both open (unsealed) and sealed versions of the miniature ball bearings are available.

Bearing with cover plates Z:

The cover plates, manufactured from sheet steel, are primarily suited to applications where the i-race of the bearing rotates. There is a sealing gap between the outer edge of the plate and the i-race. The clearance between the cover plate and the i-race is designed in such a way that no contact can be made, even if the bearing exhibits a large amount of radial play. To prevent corrosion, the cover plates are galvanized.

Bearing with low-friction seals RSL, RZ:

These non-contact seals are made from oil-resistant and wear-resistant nitrile butadiene rubber (NBR) with sheet steel reinforcement. There is a very narrow clearance between the seal and the i-race, which prevents contact between the two components. This allows bearings with low-friction seals to be used at high speeds in the same manner as bearings with Z-seals, although the former offer better sealing performance.

Bearing with contact seals RSH, RS1:

Contact seals are made from nitrile butadiene rubber (NBR) with sheet steel reinforcement. The seals are fitted in the recesses of the o-race. In contrast to the low-friction seal, the contact seal makes contact with the i-race. The contact seal prevents the ingress of any dust or moisture into the bearing.

Characteristics

Series: 62

Type: 607

Execution: Single row

Material: Steel

Sealing: Closure on one side

With flange: No

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Internal clearance	Cage	Article
624-Z	4	13	5	CN (normal)	Steel	23772463
625-Z	5	16	5	CN (normal)	Steel	23758731
626-ZTN9/LT	6	19	6	CN (normal)	Plastic	24002571
626-Z	6	19	6	CN (normal)	Steel	23758742
626-RSH	6	19	6	CN (normal)	Steel	23758741
607-ZTN9/LT	7	19	6	CN (normal)	Plastic	24002350
607-Z	7	19	6	CN (normal)	Steel	23757907
607-RSH	7	19	6	CN (normal)	Steel	24002349
627-ZTN9/LT	7	22	7	CN (normal)	Plastic	23758753
627-Z	7	22	7	CN (normal)	Steel	23758752
608-Z/C3	8	22	7	C3	Steel	23757928
608-ZTN9/LT	8	22	7	CN (normal)	Plastic	23757929
608-Z	8	22	7	CN (normal)	Steel	23757927
608-RSH	8	22	7	CN (normal)	Steel	23757926

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Internal clearance	Cage	Article
628/9-Z	9	17	5	CN (normal)	Steel	13198261
609-Z	9	24	7	CN (normal)	Steel	23757940
609-RSH	9	24	7	CN (normal)	Steel	23757939
629-Z	9	26	8	CN (normal)	Steel	23758770

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.