



## SKF Single row deep groove ball bearing Stainless steel Closure on one side

Stainless steel deep groove ball bearings are resistant to corrosion which may occur due to humidity. These single-row deep groove ball bearings are extremely versatile. They are simple in design, suitable for high to very high speeds, very robust and thus low-maintenance. Thanks to the deep grooves and the close contact between the grooves and the balls, deep groove ball bearings are extremely well suited to tolerate both radial loads and axial loads in both directions, even at high speeds. Stainless steel deep groove ball bearings have the same operating characteristics as conventional deep groove ball bearings made of steel, but have a lower load capacity. Both open (unsealed) and sealed versions of the single-row deep groove ball bearings are available.

### Bearing with cover plates Z:

The cover plates, manufactured from sheet steel, are primarily suited to applications where the i-race of the bearing rotates. There is a sealing gap between the outer edge of the plate and the i-race. The clearance between the cover plate and the i-race is designed in such a way that no contact can be made, even if the bearing exhibits a large amount of radial play. To prevent corrosion, the cover plates are galvanized.

### Bearing with contact seals RSH, RS1:

Contact seals are made from nitrile butadiene rubber (NBR) with sheet steel reinforcement. The seals are fitted in the recesses of the o-race. In contrast to the low-friction seal, the contact seal makes contact with the i-race. The contact seal prevents the ingress of any dust or moisture into the bearing.

### Characteristics

**Series:** 619

**Type:** 61900

**Execution:** Single row

**Material:** Stainless steel

**Sealing:** Closure on one side

### Application

- Recommended in: Food & Beverages

| Manufacturer ID | Inner diameter<br>mm | Outer diameter<br>mm | Width<br>mm | Internal clearance | Cage            | Article  |
|-----------------|----------------------|----------------------|-------------|--------------------|-----------------|----------|
| W 619/9-Z/W64   | 9                    | 20                   | 6           | CN (normal)        | Stainless steel | 13201745 |
| W 61900-Z/W64F  | 10                   | 22                   | 6           | CN (normal)        | Stainless steel | 13701286 |
| W 61900-Z/W64   | 10                   | 22                   | 6           | CN (normal)        | Stainless steel | 24004665 |
| W 6001-RS1/W64  | 12                   | 28                   | 8           | CN (normal)        | Stainless steel | 13201708 |
| W 6202-Z/W64L   | 15                   | 35                   | 11          | CN (normal)        | Stainless steel | 13201760 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.