

ERIKS Oil Seal type GV


Characteristics

Norm design: DIN 3760-C

Material lip: NBR

Material surface: Metal

Equivalent Types: 303, 45, L2, WC, T2 SL, SA[2], AA, B2, CRWH1, C, C1N#, DB/AA, [TR]B, AB/DB, R1, OSC, DFK, 824N



Shaft diameter	Housing diameter	Article
mm	mm	
35	62	10008264
35	72	10008265
40	56	10008267
40	62	10008270
40	62	11031513
50	68	10008274
50	70	10008275
50	72	10005389
50	90	10008280
60	90	10008282
70	90	10008286
72	90	10005499
78	95	10008287
80	100	10009096
80	110	10007049
90	110	10007050
115	140	10009650
120	140	10009651
125	160	10009656
130	160	10009657
135	160	10009658
139.7	171.4	11461238
150	170	10009660

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Shaft diameter	Housing diameter	Article
mm	mm	
150	180	10008380
160	190	10009662
170	200	10008399
170	200	10009663
180	200	10009664
180	210	10009665
195	220	10009666
195	230	10009667
230	255	10009668
260	290	10009669
260	300	10008469
265	290	10009670
280	310	10009671
400	450	10009672
500	540	10009673
500	550	10009674
560	610	10009675
600	640	10009676

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.