



ASCO Solenoid valve 2/2 Type: 32205 series 210 brass internal thread

Characteristics

Series: 210
Type: 32205
Function: Normally closed (NC)
Actuation: Indirect-acting
Electrical connection: Plug EN 175301-803 type A
Max. viscosity: 65 mm²/s
Housing material: Brass
Sealing: NBR
Material coil housing: Epoxy
Material shorting ring: Copper
Membrane material: NBR
Working time: 100 %
Level of protection (IP value): IP65

Emergency manual operation: None

Explosion-proof: No


SIL certified: No

Medium temperature: From -20 °C to 85 °C

Ambient temperature: From -20 °C to 75 °C

Application

- Water.
- Hydraulic oil.
- Neutral fluids.
- Neutrale gases.



Size table:

Type	Size	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
D402AC	1/2"	80	45	28	70	39	58	101	0.9
D402DC	1/2"	86	50	30	70	45	58	111	0.9
D002DC	1/2"	86	50	30	70	45	58	116	0.9
D409AC	3/4"	80	45	28	71	39	58	109	0.9
D009AC	3/4"	81	45	27	71	39	58	109	0.8
D409DC	3/4"	86	51	30	71	45	58	119	0.9
D401AC	3/8"	80	45	28	70	39	58	101	0.9
D401DC	3/8"	86	50	30	70	45	58	111	0.9
D001DC	3/8"	86	50	30	70	45	58	116	0.9

Maximum pressure difference table

Size	dP ^{min}	dP ^{max} Water		dP ^{max} Gas		dP ^{max} Oil	
		V AC	V DC	V AC	V DC	V AC	V DC
3/8"	0.35 bar	9 bar	14 bar	7 bar	10 bar	7 bar	10 bar
1/2"	0.35 bar	9 bar	14 bar	7 bar	10 bar	7 bar	10 bar
3/4"	0.35 bar	7 bar	9 bar	6 bar	9 bar	6 bar	9 bar

Size process connection	Process connection	Orifice mm	Kvs value m ³ /h	Minimum pressure difference bar	Maximum pressure difference bar	Coil type	Supply voltage	Power	Starting power	Article
1/2" [15]	Internal thread (BSPP)	16	3.4	0.35	16	400325-101	24V AC	6 W / 15.6 VA	34 VA	14545536
1/2" [15]	Internal thread (BSPP)	16	3.4	0.35	10	400425-142	24V DC	9 W (hot) - 11.2 W (cold)		14545537

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Article
		mm	m³/h	bar	bar					
1/2" (15)	Internal thread (BSPP)	16	3.4	0.35	7	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		11352293
1/2" (15)	Internal thread (BSPP)	16	3.4	0.35	16	400325-118	115V AC	6 W / 15.6 VA	34 VA	14545539
1/2" (15)	Internal thread (BSPP)	16	3.4	0.35	16	400325-117	230V AC	6 W / 15.6 VA	34 VA	14545538
3/4" (20)	Internal thread (BSPP)	19	4.3	0.35	16	400325-101	24V AC	6 W / 15.6 VA	34 VA	14545540
3/4" (20)	Internal thread (BSPP)	19	4.3	0.35	9	400325-101	24V AC	6 W / 15.6 VA	34 VA	11815124
3/4" (20)	Internal thread (BSPP)	19	4.3	0.35	10	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		14545542
3/4" (20)	Internal thread (BSPP)	19	4.3	0.35	16	400325-117	230V AC	6 W / 15.6 VA	34 VA	14545541
3/8" (10)	Internal thread (BSPP)	16	2.6	0.35	16	400325-117	24V AC	6 W / 15.6 VA	34 VA	14545533
3/8" (10)	Internal thread (BSPP)	16	2.6	0.35	10	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		14545535
3/8" (10)	Internal thread (BSPP)	16	2.6	0.35	7	400425-142	24V DC	9 W [hot] - 11.2 W [cold]		12159944
3/8" (10)	Internal thread (BSPP)	16	2.6	0.35	16	400325-117	230V AC	6 W / 15.6 VA	34 VA	14545534

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.