

EUROFLUID NG6 cast mounting plate EM (S) 213



Characteristics

Size: NG6/Cetop 3

Material: Cast iron

Position P and T: End

Position A and B: Side

Max. operating pressure: 310 bar

Connections: P,T: 1/2" BSP A,B 3/8" BSP



Number of valves	Prepared for relief valve	Prepared for 2/2 valve?	Article
1	No	No	12564047
1	Yes	No	12564060
1	Yes	Yes	12564085
2	No	No	12564048
2	Yes	No	12564061
2	Yes	Yes	12564086
2	No	No	1021263
3	No	No	12564049
3	Yes	No	12564062
3	Yes	Yes	12564087
3	No	No	12564058
4	No	No	12564236
4	Yes	No	12564063
4	Yes	Yes	12564088
4	No	No	12564059
5	No	No	12564050
5	Yes	No	12564064
5	Yes	Yes	12564089
6	No	No	12564051
6	Yes	No	12564065
6	Yes	Yes	12564090
7	No	No	12564052
7	Yes	No	12564066
7	Yes	Yes	12564091
8	No	No	12564053
8	Yes	No	12564067
8	Yes	Yes	12564092
9	No	No	12564054
9	Yes	No	12564068
9	Yes	Yes	12564093
10	No	No	12564055
10	Yes	No	12564069
10	Yes	Yes	12564094

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of valves	Prepared for relief valve	Prepared for 2/2 valve?	Article
11	No	No	12564056
12	No	No	12564057

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.