



BOSCH REXROTH Ball transfer unit Corrosion resistant steel Series: R0530 6

- With sheet steel housing
- Extremely small ball transfer unit
- For general applications
- All parts made from corrosion-resistant steel
- Balls made from 1.3541 / 1.4034

Characteristics

Series: R0530 6

Housing material: Corrosion resistant steel

Material ball: Corrosion resistant steel

Material cover: Corrosion resistant steel

Manufacturer ID	Size	Outer diameter of flange mm	Height mm	Outer diameter of ball mm	Diameter, housing mm	Flange thickness mm	Working height of ball mm	Dynamic load rating N	Static load rating N	Article
KU-N8-OFK	8	17	11.2	7.938	12.6	1.9	4.8	100	200	23550054
KU-N12-OFK	12	23.3	15.4	12	18	2.1	7.4	180	350	23550055
KU-N15-OFT	15			15.875						13207856
KU-N15-OFK	15	31	21.5	15.875	24	2.5	9.5	370	700	23550056
KU-N22-MFG	22	45	29.5	22.225	36	2.9	9.8	970	1800	23550057
KU-N30-MFG	30	55	37.5	30.162	45	3.7	13.8	1900	3000	23550058

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.