



BOSCH REXROTH Ball transfer unit spring-loaded Steel, galvanized Series: R0532 2

- Spring-loaded
- Ball Transfer Units are supported on springs and mounted under preload in a housing
- Ball Transfer Unit recedes into its housing under high loads
- All parts galvanized
- With cup springs

Characteristics

Series: R0532 2

Housing material: Steel, galvanized

Material ball: Corrosion resistant steel

Material cover: Steel, galvanized

Manufacturer ID	Size	Outer diameter of flange mm	Height mm	Outer diameter of ball mm	Diameter, housing mm	Flange thickness mm	Working height of ball mm	Dynamic load rating N	Static load rating N	Article
KUF-C22-TF-MFG	22	38.8	58.1	22.225	50	13.6	18.6	730	860	23550080
KUF-C30-TF-MFG	30	48.2	70	30.162	62	17	24.4	1350	1600	23550081
KUF-C45-TF-MFG	45	66.2	100.5	44.45	85	24.2	35.6	2280	2770	23550082

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.