



BOSCH REXROTH Ball transfer unit Sheet steel, galvanized Series: R0535 2

- With sheet steel housing
- Reinforced housing and cover
- For heavy impact loads
- All parts galvanized
- Balls made from corrosion-resistant steel 1.3541 / 1.4034

Characteristics

Series: R0535 2

Housing material: Sheet steel, galvanized

Material ball: Corrosion resistant steel

Material cover: Sheet steel, galvanized

Manufacturer ID	Size	Outer diameter of flange mm	Height mm	Outer diameter of ball mm	Diameter, housing mm	Flange thickness mm	Working height of ball mm	Dynamic load rating N	Static load rating N	Article
KUS-C15-MFG	15	31	21.5	15.875	24	5.5	9.5	370	700	23550101
KUS-C22-MFG	22	45	29.5	22.225	36	6.2	9.8	970	1800	23550102
KUS-C30-MFG	30	55	37.5	30.162	45	8.2	13.8	1900	4000	23550103
KUS-C45-MFG	45	75	53.7	44.45	62	10.5	19	4500	9000	23550104

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.