



FENNER QD:FLOW inverter IP66

The Fenner QD:FLOW sets a new standard for dedicated fan and pump control whilst retaining the ease of use expected from Fenner Inverters. Fenner QD:FLOW has an innovative design, combined with robust performance to provide powerful flow control and reliability in a compact drive.

Characteristics

Series: QD

Type: FLOW

Application

Multiple Fan Operation

- ◆ All drives operate as variable speed for maximum energy saving.◆ Equal run time sharing across each fan / fan bank.◆ Automatic system reconfiguration in the event of a fan fault.◆ Continued system operation when drives are individually powered off.◆ Communications and +24V control voltage shared between drives via a standard RJ45 patch lead.◆ Independent maintenance indicators for each fan bank.◆ Any fan bank can be switched to hand operation at the touch of a button and will automatically rejoin the network when switched back to auto. Recommended in: Food & Beverages

Technical Information

- ◆ Only 14 basic parameters.◆ Internal RFI filter.◆ Belt brake detection.◆ Anti-ragging function.◆ Modbus and BACnet as standard.◆ Fire-mode.◆ Spin start.◆ Bypass mode.

Construction

- ◆ IP55 and IP66 enclosures.◆ Energy optimisation.◆ Energy monitoring.◆ Pump cascade control.◆ Resonance avoidance.◆ Maintenance interval timer

Execution

- ◆ Variable Torque 0,75kW - 250 kW◆ High Quality Long-life Fans.◆ Multiple fan operation

Supply voltage	Input Phases	Type of load	Output current	Motor power	Braking Chopper	Degree of protection (IP)	Safe Torque Off	Article
V			A	kW				
380 - 480	3	Variable	2.2	0.75	No	IP66	No	13364583
380 - 480	3	Variable	2.2	0.75	No	IP66	No	13364584
380 - 480	3	Variable	4	1.5	No	IP66	No	13364585
380 - 480	3	Variable	4	1.5	No	IP66	No	13364586
380 - 480	3	Variable	5.8	2.2	No	IP66	No	13364588
380 - 480	3	Variable	5.8	2.2	No	IP66	No	13364587
380 - 480	3	Variable	7	11	No	IP66	No	13364608
380 - 480	3	Variable	9.5	4	No	IP66	No	13364593
380 - 480	3	Variable	9.5	4	No	IP66	No	13364594
380 - 480	3	Variable	14	5.5	No	IP66	No	13364595
380 - 480	3	Variable	14	5.5	No	IP66	No	13364599
380 - 480	3	Variable	14	5.5	No	IP66	No	13364598
380 - 480	3	Variable	18	7.5	No	IP66	No	13364603
380 - 480	3	Variable	18	7.5	No	IP66	Yes	13364604
380 - 480	3	Variable	24	11	No	IP66	No	13364609

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.