




CONACO Y-filter Type: 1175 Stainless steel Flange Class 150

Characteristics

Type: 1175

Norm: ASME

Housing material: Stainless steel

Connection: Flange

Flange finish: Raised face

Face to Face norm: ASME B16.10

Filter element material: Stainless steel

Material cover gasket: Graphite spiral wounded

Material drain plug: ASTM A182 F316

Minimum medium temperature (continuous): -29 °C

Maximum medium temperature (continuous): 538 °C

Maximum pressure difference at 20 °C: 1 bar

Technical Information

- Horizontal piping
- Vertical piping with downwards flow
- Maximum differential pressure 0.5bar
- Suitable for suction and delivery piping
- With drain plug as standard

Options

- Available with other perforations
- Available with material certificate EN 10204 3.1
- Available with magnet

Application

- Gases, steam, water, oil and other process fluids
- Recommended in: Chemical

Material quality	Nominal inner diameter	Pressure rating	Face to Face length	Perforation size	With measuring connections	Cover model	With drain plug	Material cover	Article
			mm	mm					
ASTM A351 CF8M	1/2" [15]	Class 150	146	0.8	No	Flanged	Yes	ASTM A351 CF8M	10059069
ASTM A351 CF8M	3/4" [20]	Class 150	172	0.8	No	Flanged	Yes	ASTM A351 CF8M	13383505
ASTM A351 CF8M	1" [25]	Class 150	197	0.8	No	Flanged	Yes	ASTM A351 CF8M	13383506
ASTM A351 CF8M	1.1/2" [40]	Class 150	219	0.8	No	Flanged	Yes	ASTM A351 CF8M	10059071
ASTM A351 CF8M	2" [50]	Class 150	203	1.5	No	Flanged	Yes	ASTM A351 CF8M	12997151
ASTM A351 CF8M	3" [80]	Class 150	241	1.5	No	Flanged	Yes	ASTM A351 CF8M	13383507
ASTM A351 CF8M	4" [100]	Class 150	292	1.5	No	Flanged	Yes	ASTM A351 CF8M	13383508
ASTM A351 CF8M	6" [150]	Class 150	406	1.5	No	Flanged	Yes	ASTM A351 CF8M	13383509
ASTM A351 CF8M	8" [200]	Class 150	495	1.5	No	Flanged	Yes	ASTM A351 CF8M	13383510
ASTM A351 CF8M	10" [250]	Class 150	622	1.5	No	Flanged	Yes	ASTM A351 CF8M	13383511
ASTM A351 CF8M	12" [300]	Class 150	699	1.5	No	Flanged	Yes	ASTM A351 CF8M	13392154

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.