



GRUNDFOS Submersible pump Series: SLV

Characteristics

Series: SLV

Connection: Flange

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1030

Insulation class acc. to IEC: F

Discharge head	Nominal volume flow rate	Max. dimension of fixed parts	Supply voltage	Motor power	Nominal current	Connection size	Pump height	Article
m	m³/h	mm		kW	A		mm	
2.9	18.4	65	3 x 400-415V AC	1.4	2.8	DN65	510	23499191
7.5	24.5	65	1 x 230V AC	1.3	6.1	DN65	510	23499188
7.5	24.5	65	1 x 230V AC	1.3	6.1	DN65	510	23499187
7.5	24.5	65	1 x 230V AC	1.3	6.1	DN65	510	23499189
7.5	24.5	65	3 x 400-415V AC	1.4	2.8	DN65	510	23499192
7.5	24.5	65	3 x 400-415V AC	1.4	2.8	DN65	510	23499190
9.5	42.8	65	1 x 230V AC	1.6	7.4	DN65	510	23499065
9.5	42.8	65	1 x 230V AC	1.6	7.4	DN65	510	23499066
9.5	42.8	65	1 x 230V AC	1.6	7.4	DN65	510	23499067
9.5	42.8	65	3 x 400-415V AC	1.6	3.1	DN65	510	23499070
9.5	42.8	65	3 x 400-415V AC	1.6	3.1	DN65	510	23499068
9.5	42.8	65	3 x 400-415V AC	1.6	3.1	DN65	510	23499069
10.6	45	65	3 x 400-415V AC	2.2	3.8	DN65	510	23499023
10.6	45	65	3 x 400-415V AC	2.2	3.8	DN65	510	23499024
10.6	45	65	3 x 400-415V AC	2.2	3.8	DN65	510	23499025

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.