



FLEXION Push in fitting nickel plated brass branch tee BSPP (G)

Characteristics

- Type:** MPD
- Material:** Brass, Nickel-plated
- Operating temperature:** -20 / 80 °C
- Operating pressure:** -0.99 / 18 bar

Manufacturer ID	Tube Outside Diameter mm	Thread type	Thread size	Article
MPD4-G01-FX	4	External thread BSPP (G)	1/8	14059849
MPD6-G02-FX	6	External thread BSPP (G)	1/4	14059852
MPD6-G01-FX	6	External thread BSPP (G)	1/8	14059851
MPD8-G02-FX	8	External thread BSPP (G)	1/4	14059854
MPD8-G01-FX	8	External thread BSPP (G)	1/8	14059853
MPD10-G02-FX	10	External thread BSPP (G)	1/4	14059855
MPD10-G03-FX	10	External thread BSPP (G)	3/8	14059856
MPD12-G04-FX	12	External thread BSPP (G)	1/2	14059858
MPD12-G03-FX	12	External thread BSPP (G)	3/8	14059857

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.