



AVENTICS 5/2-directional valve Series CD07

Characteristics

- Series:** CD07
- Operation:** Pneumatic
- Type of body:** Body Ported
- Housing material:** Zinc die-casting
- Seal material:** NBR

Flow Rate (6 bar - delta p = 1 bar) NI/min	Port thread type	Port Size in	Operating pressure bar	Maximum operating pressure bar	Function	Pilot supply	Operating voltage	Electrical connection	Protection class	Article
1200	BSPP (G)	1/4	-0.95 / 10	10	5/2	External	24V DC	Plug EN 175301-803 type A	IP65	24105062
1200	BSPP (G)	1/4	3 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	12107872
1200	BSPP (G)	1/4	2 / 10	10	5/2	Internal	24V DC	Plug EN 175301-803 type A	IP65	12351265
1200	BSPP (G)	1/4	-0.95 / 10	10	5/2					12670172
1200	BSPP (G)	1/4	-0.95 / 10	10	5/2					12396629
1200	BSPP (G)	1/4	-0.95 / 10	10	5/2					11954906

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.