



AVENTICS 3/2-directional valve Series ST

Characteristics

Series: ST
Maximum operating pressure [Bar]: 10 bar
Operation: Pneumatic
Type of body: Body Ported
Housing material: Stainless steel

Flow Rate (6 bar - delta p = 1 bar) NI/min	Port thread type	Port Size in	Operating pressure bar	Function	Pilot supply	Operating voltage	Electrical connection	Protection class	Seal material	Article
280	BSPP (G)	1/8	2 / 10	3/2 Normally closed	Internal	24V DC	Plug ISO 15217 type C	IP65	NBR	13517438
280	BSPP (G)	1/8	-0.95 / 10	3/2						24104543
280	BSPP (G)	1/8	-0.95 / 10	3/2						12103499
280	BSPP (G)	1/8	-0.95 / 10	3/2 Normally closed						24035906
280	BSPP (G)	1/8	-0.95 / 10	3/2 Normally closed						12570940
280	BSPP (G)	1/8	-0.95 / 10	3/2 Normally closed						24104542
280	BSPP (G)	1/8	-0.95 / 10	3/2 Normally closed					NBR	23575399

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.