

AVENTICS 3/2-directional valve Series AP



Characteristics

Series: AP
Operation: Mechanical
Type of body: Body Ported

Flow rate at 6 Bar	Flow Rate (6 bar - delta p = 1 bar)	Port thread type	Port Size	Port Size	Operating pressure	Maximum operating pressure	Function	Housing material	Seal material	Article
l/min	NI/min		in	mm	bar	bar				
	550	BSPP [G]	1/4		0 / 10	10	3/2 Normally closed	Aluminium	NBR	11303058
	550	BSPP [G]	1/4		0 / 10	10	3/2 Normally closed	Aluminium	NBR	24104535
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	12243868
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	24104552
190		Metric		M 5	0 / 10	10	3/2 Normally closed	Aluminium	NBR	12243863
250		BSPP [G]	1/8		0 / 10	10	3/2 Normally closed	Aluminium	NBR	12398914
250		BSPP [G]	1/8		0 / 10	10	3/2 Normally closed	Aluminium	NBR	12612168

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.