



SMC 3/2-way Ball Valve series VHS

- Increased flow-rate characteristics up to 45%
- PBT resin or Aluminium handle and bonnet
- No air bleeding during switching the handle
- Double action new sizes: VHS2510 and VHS3510
- Built-in silencer [EXH port]

Characteristics

Series: AC-A

Type: VHS

Operation: Manual

Operating temperature: -5 / 60 °C

Spool material: PBT

Handle material: PBT

Fluid: Compressed air

Norm: OSHA

Port thread type	Port Size in	Operating pressure bar	Maximum operating pressure bar	Maximum operating pressure MPa	Function	Construction size	Housing material	Seal material	Article
									12620991
									12388676
									12365155
BSPP (G)	1/4	1 / 10	10	1	3/2	30	Aluminium die-cast	HNBR	12532043
BSPP (G)	1/4	1 / 10	10	1	3/2	20	Aluminium die-cast	HNBR	11965717
BSPP (G)	1/8	1 / 10	10	1	3/2	20	Aluminium die-cast	HNBR	14069508

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.