

## ECON® Pressure gauge valve Type 861 brass internal/external thread

## **Characteristics**

**Type:** 861

Housing material: Brass
Operation: Hand wheel
Material tension socket: Steel
Material swivel nut: Steel



Type 1



	rocess inection	Size process connection	Connection instrument side	Size instrument connection	Inspection connection	Pressure rating	Maximum pressure at 20°C bar	Maximum medium temperature (continuous) °C	Primary spindle seal material	Spindle material	Article
Г	utarnal		Tonsion				Dai				
	xternal hread	1/2" BSPP(G)	Tension socket	1/2" BSPP(G)	M20x1.5	PN250	250	120	PTFE	1.4101	12725860
	xternal hread	1/2" BSPP(G)	Tension socket	1/2" BSPP[G]	None	PN250	250	120	PTFE	1.4104	11811722
ι	nread	, , ,	socket	, , ,							
	xternal hread	1/4" BSPP(G)	Tension socket	1/4" BSPP(G)	None	PN125	125	120	PTFE	1.4104	11811723

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**ERIKS** 

PR1439386003279\_EN\_18.05.2024